

may 2015



Mini Reglette

code
5230

Technical description

High output luminaire for general lighting designed to use LED lamps. Extruded aluminium component-holding box complete with plastic flow director designed to optimise light distribution. Polycarbonate safety screen as standard. Couplings for direct elect

Installation

Ceiling- and wall-mounted.

Size (mm)

598x26x38

Colour

Aluminium (12)

Mounting

wall surface | ceiling surface

Wiring info

product complete with electronic components

Complies with EN60598-1 and pertinent regulations



Product configuration: 5230+LED

LED: LED Warm

Product characteristics

Total lighting output [Lm]: 720
Total power [W]: 10
Luminous efficacy (lm/W): 72
Life Time: 40.000h - L70 (Ta 25°C)

Total luminous flux at or above an angle of 90° [Lm]: 111.38
Emergency luminous flux [Lm]: /
Voltage [V]: -
Number of optical assemblies: 1

Optical assembly Characteristics 1

Light Output Ratio (L.O.R.) [%]: 100
Lamp code: LED
ZVEI Code: LED
Nominal power [W]: 10
Nominal luminous [Lm]: 720
Lamp maximum intensity [cd]: /
Beam angle [°]: /

Number of lamps for optical assembly: 1
Socket: /
Ballast losses [W]: 0
Colour temperature [K]: 3000
CRI: 80
Wavelength [nm]: /
MacAdam Step: <4

Polar

