


may 2015

**iPro****code**
BK24**Technical description**

Direct light outdoor floodlight, designed to use neutral white LED lamps, with flood optic. Ground, wall or ceiling installation using special adjustable bracket. The luminaire consists of an optical assembly, rear cap and adjustable bracket. The optical assembly and rear cap are made of die-cast aluminium alloy coated with liquid acrylic paint (grey finish) or textured liquid (white finish) with a high level of resistance to weather and UV rays. Transparent tempered sodium - calcium safety glass with customised grey serigraphy, 4 mm thick, joined to the optical assembly with silicone. Adjustable fixing bracket made of painted aluminium; with a double nickel-plated brass PG11 cable gland, suitable for power cables \varnothing 6.5-11 mm. For electrical connection the product has a plastic box with three 2-pin quick-coupling terminals for cables with max. cross-section 4 mm². Electronic circuit with neutral white LED, optics with lens made of thermoplastic material (methacrylate) and a black polycarbonate multi-groove ring for visual comfort. Equipped with electronic ballast $V_{in}=100-240V$ ac 50/60Hz. All external screws used are made of A2 stainless steel. The luminaire technical characteristics conform to EN60598-1 standards and particular requirements.

Installation

Ground, wall or ceiling installation using special bracket. Secure using screw anchors for concrete, cement and solid brick.

Size (mm)

81x81x86

Colour

White (01) | Grey (15)

Weight (kg)

0.86

Mounting

free standing

Wiring info

Equipped with electronic ballast $V_{in}=100-240V$ ac 50/60Hz. Polyamide PG11 double cable gland for pass-through wiring, suitable for power cables \varnothing 6.5-11 mm.

Notes

Product complete with LED lamp.

Complies with EN60598-1 and pertinent regulations

 960°C IK07 IP66
**Product configuration: BK24+LED**

LED: Nr. 3 LED NEUTRAL WHITE

Product characteristics

Total lighting output [Lm]: 240
Total power [W]: 6.4
Luminous efficacy (lm/W): 37.5
Life Time: 100.000h - L80 - B20 (Ta 25°C)
Number of optical assemblies: 1

Total luminous flux at or above an angle of 90° [Lm]: 0
Emergency luminous flux [Lm]: /
Voltage [V]: -
Life Time: 66.000h - L80 - B20 (Ta 40°C)

Optical assembly Characteristics 1

Light Output Ratio (L.O.R.) [%]: 60
Lamp code: LED
ZVEI Code: LED
Nominal power [W]: 4.7
Nominal luminous [Lm]: 400
Lamp maximum intensity [cd]: /
Beam angle [°]: 34°

Number of lamps for optical assembly: 1
Socket: /
Ballast losses [W]: 1.7
Colour temperature [K]: 4000
CRI: 80
Wavelength [Nm]: /
MacAdam Step: <3

Polar

